

Veneer

Dryer Seal Components

High-Quality

We make all of the seals we sell, and take pride in constructing and delivering a quality product. Dimensioned approval drawings and specifications are sent with every quote to assure that you will receive what you expect.

Fast

We understand your need to have orders filled quickly. That's why we stock every component required to construct your seals. Usually, we can ship re-orders within three to five business days of your order. Initial orders are usually delivered in less than 2 weeks.

Economical

We maintain raw material inventory, construct our seals, and support customers from a single location. That's unique in the dryer seal business, and it's one reason why we can offer superior quality and service for such a low price.

Door Seal

PTFE impregnated fiberglass sheath with stainless steel core
Nominal $\frac{3}{4}$ " bulb diameter, $\frac{3}{4}$ " tail
Other materials and dimensions are available

Door Seal Hold Down Angle

14 Ga Steel, $\frac{3}{8}$ " x $\frac{3}{4}$ " angle, slotted holes

Dryer Body and Upper-Duct Expansion Joint

Double-layer aluminum-laminated fiberglass
 $\frac{3}{4}$ " stainless steel bulbs
Standard widths from 8" to 32", made to order lengths

Round-Duct Expansion Joint

Double-layer aluminum-laminated fiberglass
Standard widths of 12", 15", and 18", made to order lengths
Custom widths available
Duct clamps available